

## Industrial Pressure Washers ....Built Right to Do the Job Right

## **Portable, Gasoline-Powered,** Cold Water Pressure Washer

■ Up to 3.8 GPM; Up to 4000 PSI

- Direct-Drive Pump with 7-year Warranty
- Reliable Honda Engine
- E-Z Pull Starting
- Detergent Injection

■ Insulated, fatigue-free, springloaded **Trigger Gun** with twopiece, easy-grip **Spray Wand** make for easy point-and-shoot cleaning action.



Industrial-duty Gasoline-Powered Honda Engine with 3-year warranty, overhead valves and easy-access oil drain line.

Illustrated Labels with universal graphics and symbols make operating instructions and warnings easy to understand for operator convenience and owner liability protection.

Industrial-grade, directdrive High-Pressure Pump has a tri-plex, forged brass head with a seven-year warranty and E-Z Start Valve for resistance-free pull starting of the 265cc and 389cc engines.

Many Safety Features, including a thermal pump protector to prevent the build up of excessive pressures or heat.

Rugged 10-gauge steel Chassis is protected by an all-weather, epoxy powder coat finish.

■ 50 ft. of steel-wire braid High Pressure Hose with 24-inch Hose Guard for burst protection and swivel Crimp Fitting for tangle-free handling of hose and trigger gun.



Two Rubber Pad Feet absorb vibration for long life and keep the unit from "walking."

■ Four quick-couple **Nozzles** are made of hardened stainless steel and color-coded for easy selection of spray pattern: 0°, 15°, 25°, 40°. ■ Easy-to-attach **Detergent** Injector and Soap Nozzle for easy application of detergents

10 in. 4-ply, tubed Pneumatic Tires make for easy maneuvering in any terrain. ■ Convenient Hose and Gun Hanger makes for easy storage of hose and trigger gun.







## WHY CHOOSE THE PC?

Like the PG models, the PC cold-water pressure washers offer an array of options and features for cleaning multiple surfaces indoors and outdoors, but utilize direct-drive instead of belt-drive pumps. Each comes equipped with 50' of Landa Kärcher Group's durable wire-braid high-pressure hose, and a thermal pump protector to prevent overheating while in bypass mode. Shockabsorbing rubber feet reduce vibration and prevent movement during operation, and handles on the front and back make these machines a breeze to load and unload.

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Wt (lbs)
PC3-24324	1.107-005.0	2.3	2400	3200	Honda GX160	163	130
PC3-27324	1.107-006.0	2.5	2700	3200	Honda GX200	196	135
PC4-35324	1.107-008.0	3.8	3500	3200	Honda GX390	389	185
PC4-40324	1.107-224.0	3.5	4000	3200	Honda GX390	389	188

## Distributed by: